



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

PLUMBING MECHANICAL PLUGS

GRIPPER® MECHANICAL PLUGS

- Ideal for plumbing system tests
- Easy to install with extra-large wing nut
- Inside of pipe seals inside pipe as far as needed
- Made with glass-reinforced ABS plastic
- End-of-pipe seals only at the end of a pipe, preventing plug from falling into stack



270 210	1-1/2"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 229	2"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 237	3"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 245	4"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 261	6"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 270	8"	End of Pipe Gripper® Plug	10	17 PSI	40 FT
270 296	4"	Inside of Pipe Gripper® Plug	10	17 PSI	40 FT
270 253	6"	Inside of Pipe Gripper® Plug	10	17 PSI	40 FT
270 288	8"	Inside of Pipe Gripper® Plug	10	17 PSI	40 FT

HUB-FIT GRIPPER® PLUGS

- Ideal for use in hub fittings and in bell-end pipe
- Pressure rated for conducting DWV tests
- Yellow color enhances visibility in pipe
- Made with glass-reinforced ABS plastic and natural rubber O-ring



270 528	2"	Hub-Fit Gripper® Plug	10	13 PSI	30 FT
270 538	3"	Hub-Fit Gripper® Plug	10	13 PSI	30 FT
270 548	4"	Hub-Fit Gripper® Plug	10	13 PSI	30 FT

CLEAN-OUT GRIPPER® PLUGS

- Patented threaded O-ring ensures airtight seal
- Stainless steel hardware prevents corrosion
- Black color blends well with cast-iron pipe
- NPT-sized, including hard-to-find 3-1/2"
- Guaranteed to seal all damaged threads
- Made with glass-reinforced ABS plastic and natural rubber O-ring



270 168	2"	Clean-Out Gripper® Plug	10	17 PSI	40 FT
270 178	3"	Clean-Out Gripper® Plug	10	17 PSI	40 FT
270 138	3-1/2"	Clean-Out Gripper® Plug	10	17 PSI	40 FT
270 188	4"	Clean-Out Gripper® Plug	10	17 PSI	40 FT



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

IRON GRIP™ MECHANICAL BY-PASS PLUGS

- Wing-nut design allows for easy installation with tools
- Can be used as a permanent or temporary plug
- Cast-iron bypass design can be used for water test or sewer air testing



268 028	2"	Iron Grip™ Plug - 3/8" Bypass	1	13 PSI	30 FT
268 038	3"	Iron Grip™ Plug - 1/2" Bypass	1	11 PSI	25 FT
268 048	4"	Iron Grip™ Plug - 1/2" Bypass	1	8.7 PSI	20 FT
268 068	6"	Iron Grip™ Plug - 1/2" Bypass	1	4.3 PSI	10 FT
268 088	8"	Iron Grip™ Plug - 1/2" Bypass	1	4.3 PSI	10 FT
268 108	10"	Iron Grip™ Plug - 1/2" Bypass	1	3.5 PSI	8 FT
268 128	12"	Iron Grip™ Plug - 1" Bypass	1	2.6 PSI	6 FT

ECON-O-GRIP® PLUGS

- Cost-effective method for plugging open-ended pipe
- Natural rubber O-ring
- Effective pipe dust cover
- Not recommended for pressure tests

271 519	1-1/2"	Econ-O-Grip® Plug	10	2 PSI	5 FT
271 527	2"	Econ-O-Grip® Plug	10	2 PSI	5 FT
271 535	3"	Econ-O-Grip® Plug	10	2 PSI	5 FT
271 543	4"	Econ-O-Grip® Plug	10	2 PSI	5 FT
271 551	5"	Econ-O-Grip® Plug	5	1 PSI	2 FT
271 578	6"	Econ-O-Grip® Plug	5	1 PSI	2 FT



PETRO ECON-O-GRIP® PLUGS (CHEMICAL RESISTANT)

- Chemical-resistant Nitrile rubber and stainless steel hardware
- Not recommended for pressure tests

273 318	1-1/2"	Stainless Steel Econ-O-Grip® Plug	2	2 PSI	5 FT
273 328	2"	Stainless Steel Econ-O-Grip® Plug	2	2 PSI	5 FT
273 338	3"	Stainless Steel Econ-O-Grip® Plug	2	2 PSI	5 FT
273 348	4"	Stainless Steel Econ-O-Grip® Plug	2	2 PSI	5 FT
273 358	5"	Stainless Steel Econ-O-Grip® Plug	1	1 PSI	2 FT
273 368	6"	Stainless Steel Econ-O-Grip® Plug	1	1 PSI	2 FT



SURE-GRIP® PLUGS - NEW DESIGN!

- Polypropylene construction with natural rubber O-ring
- Can be used as a permanent or temporary plug
- Fits all type of pipe at nominal sizes

271 158	1-1/2"	Sure-Grip® Plug	10	22 PSI	50 FT
271 208	2"	Sure-Grip® Plug	10	22 PSI	50 FT
271 308	3"	Sure-Grip® Plug	10	13 PSI	30 FT
271 408	4"	Sure-Grip® Plug	10	13 PSI	30 FT



Category 12 cherne Mechanicals

12



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

KWIK 'N SURE® PLUGS

- Works in all types of pipe
- Works well for plugging water line stub-outs
- Wing nut on 3/8" - 1-1/4" sizes
- Natural rubber O-ring
- Hex nut on 1.5" through 5" sizes

269 832	0.39"	Kwik 'n Sure Plug	1	185 PSI	428 FT
269 840	1/2"	Kwik 'n Sure Plug	1	180 PSI	415 FT
269 867	3/4"	Kwik 'n Sure Plug	1	180 PSI	415 FT
269 875	1"	Kwik 'n Sure Plug	1	40 PSI	92 FT
269 883	1-1/4"	Kwik 'n Sure Plug	1	112 PSI	258 FT
269 891	1-1/2"	Kwik 'n Sure Plug	1	88 PSI	203 FT
269 905	2"	Kwik 'n Sure Plug	1	112 PSI	258 FT
269 913	2-1/2"	Kwik 'n Sure Plug	1	72 PSI	166 FT
269 921	3"	Kwik 'n Sure Plug	1	28 PSI	65 FT
269 948	4"	Kwik 'n Sure Plug	1	24 PSI	558 FT
269 956	5"	Kwik 'n Sure Plug	1	8 PSI	18 FT



MONITOR WELL® LOCKING PLUGS

- Designed to seal monitor wells
- Meets all EPA requirements for locking plugs
- Sized to seal schedule 40 piping
- Made with chemical-/petroleum-resistant Estaloc® plastic top/bottom plates and Nitrile sealing O-ring
- Comes with stainless steel carriage bolt
- 2" and 4" sizes can also seal schedule 5 plastic and stainless steel pipe
- Yellow chromate-coated locking latch accepts Cherne's solid brass padlock or No. 2 Master® padlock

271 648	1"-1-1/4"	Monitor Well® Locking Plug	12	6.5 PSI	15 FT
271 675	2"	Monitor Well® Locking Plug	50	6.5 PSI	15 FT
271 669	3"	Monitor Well® Locking Plug	75	6.5 PSI	15 FT
271 683	4"	Monitor Well® Locking Plug	25	6.5 PSI	15 FT
271 691	6"	Monitor Well® Locking Plug	8	6.5 PSI	15 FT
271 735	8"	Monitor Well® Locking Plug	1	6.5 PSI	15 FT
112 941		Padlock with Key	1	6.5 PSI	15 FT



PLASTIC TEST CAPS

- Seal pipe ends economically
- Bright yellow color adds visibility for after-test removal
- For use on schedule 40 ABS and PVC DWV pipe

238 701	1-1/2"	Knock-Out™ Test Cap	100/1500	13 PSI	30 FT
238 702	2"	Knock-Out™ Test Cap	100/1200	13 PSI	30 FT
238 703	3"	Knock-Out™ Test Cap	50/500	13 PSI	30 FT
238 704	4"	Knock-Out™ Test Cap	100/1500	13 PSI	30 FT
228 108	1-1/2"	Push-Cap™ Test Cap	50/250	4.3 PSI	10 FT
228 208	2"	Push-Cap™ Test Cap	25/125	4.3 PSI	10 FT
228 308	3"	Push-Cap™ Test Cap	10/100	4.3 PSI	10 FT
228 408	4"	Push-Cap™ Test Cap	10/50	4.3 PSI	10 FT
238 108	1-1/2"	End-Cap™ Test Cap	100/1000	17 PSI	40 FT
238 208	2"	End-Cap™ Test Cap	100/800	17 PSI	40 FT
238 308	3"	End-Cap™ Test Cap	50/400	17 PSI	40 FT
238 408	4"	End-Cap™ Test Cap	25/200	17 PSI	40 FT
238 128	1-1/2"-2"	MS End-Cap™ Test Cap	50/500	17 PSI	40 FT
238 348	3"-4"	MS End-Cap™ Test Cap	25/200	17 PSI	40 FT



PVC TEST-KAP® PLUGS

- Stainless steel hose clamp won't corrode
- Reinforced cross-molded top increases strength
- For use on plastic, steel, copper, and cast-iron pipe
- Tighten clamp with torque wrench or screwdriver to 60 inch pounds

270 725	1-1/2"	Test-Kap® Plug	1	13 PSI	30 FT
270 733	2"	Test-Kap® Plug	1	13 PSI	30 FT
270 741	3"	Test-Kap® Plug	1	13 PSI	30 FT
270 768	4"	Test-Kap® Plug	1	13 PSI	30 FT
270 776	5"	Test-Kap® Plug	1	13 PSI	30 FT
270 784	6"	Test-Kap® Plug	1	13 PSI	30 FT



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

PLUMBING ACCESSORIES

ECON-O-PUMP® TEST PUMPS

- Economical pump for inflating Test Balls
- Features 0-140 PSI gauge with protective cover
- All-steel construction for durability

273 888		Econ-O-Pump Test Pump	6		
---------	--	-----------------------	---	--	--

AIR- MAX® TEST PUMPS

- Gauge raised from base for protection
- Durable steel barrel
- Textured steel base prevents feet from slipping
- Durable, no-kink hose

273 958		Air-Max® Test Pump	1		
034 588		Replacement Hose Assembly w/ Thumb Lock	1		

AIR- MAX® HV TEST PUMPS

- Large barrel for maximum volume means fewer strokes to inflate plug
- 0-60 PSI gauge for most accurate plug pressure readings
- All-metal thumb lock for durability
- Hose strain relief to transfer tension from hose to the barrel
- Forged steel barrel for extra toughness
- Large, three-point base for maximum stability
- Rubber cover to protect gauge from damage
- Solid wood handle for greater comfort and durability
- Durable, no-kink hose

273 968		Air-Max® Pro HV Test Pump	1		
055 728		Replacement Hose Assembly w/ Thumb Lock	1		



EXTENSION HOSES

- Recommended for use with plugs up to 15"
- Ideal for plumbing applications
- Standard tire fitting connections
- 3/16" ID hose

274 011	2'	Extension Hose	6		
274 038	3'	Extension Hose	6		
274 054	5'	Extension Hose	6		
274 100	10'	Extension Hose	1		
274 208	20'	Extension Hose	1		

055 816		Deflator w/ Clamp (Female Replacement End)	1		
055 808		Inflator w/ Clamp (Male Replacement End)	1		

274 218	5'	Extension Hose w/ Gauge	1		
274 228	10'	Extension Hose w/ Gauge	1		
274 238	20'	Extension Hose w/ Gauge	1		



MANOMETER

- Used for final test of DWV pipe and to test gas lines
- Reads in 1/10" increments
- Measures water columns from 0" to 16"

010 205		Manometer	1		
---------	--	-----------	---	--	--



CLOG-BUSTER® DRAIN FLUSHER

- Unclogs drain pipes in seconds
- Simply remove aerator from faucet spigot and attach faucet adapter to garden hose
- Attaches to standard garden hose fitting
- Natural rubber body provides excellent seal

303 127	1"-2"	Drain Flusher	1		
303 135	1-1/2"-3"	Drain Flusher	1		
303 143	4"-6"	Drain Flusher	1		



Category 12 cherne Mechanicals

12



Product No.	Size	Description	Ctn. Qty.	Back Pressure P.S.I.	Feet of Head
-------------	------	-------------	-----------	----------------------	--------------

REPLACEMENT RING & CHAIN ASSEMBLIES

- Replacement assemblies for Test-Ball plugs
- Rings prevent test plugs from sliding down a line
- Includes a safety tag

059 708	2"	Ring with 12" Chain	1		
059 718	3"	Ring with 12" Chain	1		
059 728	4"	Ring with 12" Chain	1		
059 738	5"	Ring with 12" Chain	1		
059 748	6"	Ring with 12" Chain	1		
059 758	2"	Ring with 24" Chain	1		
059 768	3"	Ring with 24" Chain	1		
059 778	4"	Ring with 24" Chain	1		
059 788	5"	Ring with 24" Chain	1		
059 798	6"	Ring with 24" Chain	1		

TEST GAUGES

- Features 2" unbreakable plastic face
- All connections constructed of high-quality brass
- Inflator valve is replaceable

000 698		0-15 psi w/out test body	1		
000 628		0-30 psi w/out test body	1		
000 638		0-60 psi w/out test body	1		
000 648		0-100 psi w/out test body	1		
024 568		0-15 psi w/ hex test body	1		
019 698		0-30 psi w/ hex test body	1		
019 708		0-60 psi w/ hex test body	1		
019 718		0-100 psi w/ hex test body	1		
000 658		Hex Test Body, 1/8th Tap	1		
068 527		Replacement Snifter Valve 1/8"	1		