


Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

GALVANIZED NO-CALK® ROOF FLASHINGS

- Galvanized Base.
- Self-sealing collar slides over pipe and requires no caulking.
- Do not use petroleum based products or paint on flashing collar. Not for hot-mopped or built-up roofs.
- Metal base for pitch from 0-40° or up to 10/12 roof.
- Rated 180°F continuous heat and approved for Type B installations.



SOLAR FLASHING

11830	.5" - 1"	Galvanized	038753-118307	12	11
11831	.5" - 1"	Galvanized 18" x 18"	038753-118314	12	23

STANDARD BASE FLASHING

11840	1.25" - 1.5"	Galvanized 9" x 12.5" base	038753-118406	12	12
11855	2"	Galvanized 9" x 12.5" base	038753-118550	12	12
11866	3"	Galvanized 11" x 14.5" base	038753-118666	12	17
11879	4"	Galvanized 12" x 15" base	038753-118796	12	23

18" X 18" CODE BASE FLASHING

11921	1.25" - 1.5"	Galvanized 18" x 18"	038753-119212	12	23
11934	2"	Galvanized 18" x 18"	038753-119342	12	23
11947	3"	Galvanized 18" x 18"	038753-119472	12	23
11950	4"	Galvanized 18" x 18"	038753-119502	12	26

ALUMINUM NO-CALK® ROOF FLASHINGS

- Rustproof .032 stamped aluminum base allows for easy shaping of flashing.
- Rated 180°F continuous heat and approved for Type B installations.
- Metal base for pitch from 0-40° or up to 10/12 roof.
- Self-sealing collar slides over pipe and requires no caulking.
- Do not use petroleum based products or paint on flashing collar. Not for hot-mopped or built-up roofs.



18" X 18" CODE BASE FLASHING

12836	1.25" - 1.5"	Soft Aluminum 18" x 18"	038753-128368	12	15
12849	2"	Soft Aluminum 18" x 18"	038753-128498	12	14
48142	3"	Soft Aluminum 18" x 18"	038753-481425	12	20
48143	4"	Soft Aluminum 18" x 18"	038753-481432	12	21

THERMOPLASTIC NO-CALK® ROOF FLASHINGS

- Non-fading, non-cracking, rigid black thermoplastic base.
- Self-sealing collar slides over pipe and requires no caulking.
- Do not use petroleum based products or paint on flashing collar or plastic base. Not for hot-mopped or built-up roofs.
- Plastic base for pitch from 0-45° or up to 12/12 roof.
- Rated 180°F continuous heat and approved for Type B installations.

48100	1.25" - 1.5"	Thermoplastic	038753-481005	12	6
48101	2"	Thermoplastic	038753-481012	12	6
48102	3"	Thermoplastic	038753-481029	12	8
48103	4"	Thermoplastic	038753-481036	12	9



U.S. Patent No.
5,390,451

FLEX-FLASH™ NO-CALK® ROOF FLASHINGS

- 100% flexible, foldable plastic base.
- Self-sealing collar slides over pipe and requires no caulking.
- Do not use petroleum based products or paint on flashing collar or plastic base. Not for hot-mopped or built-up roofs.
- Plastic base for pitch from 0-45° or up to 12/12 roof.
- Rated 180°F continuous heat and approved for Type B installations.

14009	1.25" - 1.5"	Flex-Flash	038753-140094	12	6
14012	2"	Flex-Flash	038753-140124	12	7
14046	3"	Flex-Flash	038753-140469	12	9
14047	4"	Flex-Flash	038753-140476	12	13





Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

HIGH-RISE® THERMOPLASTIC ALL-FLASH® NO-CALK® ROOF FLASHINGS

- Ideal for steep pitch roofs with non-fading, non-cracking, rigid black thermoplastic base.
- Self-sealing collar slides over pipe and requires no caulking.
- Do not use petroleum based products or paint on flashing collar or plastic base. Not for hot-mopped or built-up roofs.
- Plastic base for pitch from 10-60° or up to 20/12 roof.
- Rated 180°F continuous heat and approved for Type B installations.

11930	1.5" - 3"	All-Flash Highrise Flashing	038753-119304	6	1.2
11931	3" - 4"	All-Flash Highrise Flashing	038753-119311	6	1.4

MASTER FLASH® ROOF FLASHINGS

- Engineered for profiled roofing systems at any pitch.
- Rated 212°F continuous heat and approved for Type B installations.
- Easily customized to accommodate a broad range of pipe diameters.



14050	.25" - 2"	Master Flash®	038753-140506	6	1
14051	1.25" - 3"	Master Flash®	038753-140513	6	2
14052	.25" - 4"	Master Flash®	038753-140520	6	4
14053	3" - 6"	Master Flash®	038753-140537	6	5
14054	4" - 7"	Master Flash®	038753-140544	2	3
14055	5" - 9"	Master Flash®	038753-140551	2	4
14056	6" - 11"	Master Flash®	038753-140568	2	6
14057	7" - 13"	Master Flash®	038753-140575	2	7
14059	10" - 18"	Master Flash®	038753-140599	5	23

MASTER FLASH® is a Registered Trademark of the Aztec Washer Company, Inc.

RAIN COLLAR FOR NO-CALK® ROOF FLASHINGS

- Use as a protective water shield (slides over existing flashing).
- Do not use petroleum based products on rubber collars.
- Non-fading collar material.



14122	1.25" - 1.5"	Collar	038753-141220	36	2
14205	1.25" - 1.5"	Collar	038753-142050	6	.5
14135	2"	Collar	038753-141350	24	2
14206	2"	Collar Carded	038753-142067	6	.5
14193	3"	Collar	038753-141930	24	3
14207	3"	Collar Carded	038753-142074	6	.5
14203	4"	Collar	038753-142036	12	5
14208	4"	Collar Carded	038753-142081	6	1