

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------



**PLUMBER'S PUTTY**

- Stainless fixture setting compound for setting frames, faucets, strainer baskets, etc.
- Stays flexible and will not crack or shrink.
- Made of easily workable soft, pliable material.
- Not for use on marble, granite, plastic or any other dimensional stone.
- Meets Military Spec. TT-P-1536A.

48003	14 oz.	Putty - Plastic container	038753-480039	24	24
48004	5 lb.	Putty - Plastic container	038753-480046	6	32



**PIPE/GASKET LUBE**

- Non-toxic, soft, paste like material for lubricating bell joint pipe gaskets.
- Will not deteriorate natural or synthetic rubber.
- Will not support bacteria.
- Dissolves in hot water.

30599	16 oz.	Lubricant, for rubber gaskets	038753-305998	24	30
30600	32 oz.	Lubricant, for rubber gaskets	038753-306001	12	25
30601	Gallon	Lubricant, for rubber gaskets	038753-306018	4	34
30605	5 Gallon	Lubricant, for rubber gaskets	038753-306056	1	42



**GREY PIPE JOINT COMPOUND**

- Non-hardening grey paste seals and lubricates threaded joints.
- For use on water, steam or air lines.
- Non-separating and non-toxic material.
- Not for use on plastic threads.

48005	1 fl. oz.	Pipe Joint Compound	038753-480053	12	2
48006	8 fl. oz.	Pipe Joint Compound	038753-480060	12	13
48324	16 fl. oz.	Pipe Joint Compound	038753-483245	24	46
48325	32 fl. oz.	Pipe Joint Compound	038753-483252	12	43



**GREAT WHITE® PIPE JOINT COMPOUND WITH PTFE**

- Lubricates and seals all threaded joints.
- White, non-hardening, non-separating, non-toxic paste.
- Withstands up to 3,000 PSI on gases from -50 to +400°F, and 10,000 PSI on liquids from -50 to +500°F.
- For use with water, steam, caustics or dilute acid lines.
- Can be used with plastic and metal threads.

48007	1 fl. oz.	Pipe Dope w/ Teflon®	038753-480077	12	1
48008	4 fl. oz.	Pipe Dope w/ Teflon®	038753-480084	12	7
48009	8 fl. oz.	Pipe Dope w/ Teflon®	038753-480091	12	12
48321	16 fl. oz.	Pipe Dope w/ Teflon®	038753-483214	24	39
48322	32 fl. oz.	Pipe Dope w/ Teflon®	038753-483221	12	40

\*Teflon is a registered trademark of Dupont Fluorocarbon Resins.



**GREAT BLUE® PIPE JOINT COMPOUND**

- Flexible blue, non-hardening, non-separating, non-toxic paste, no odor, easy clean-up.
- Use on PVC, CPVC, ABS, polyethylene, polypropylene, iron, steel, copper or brass threads up to and including 2".
- Withstands up to 3,000 PSI on gases from -50° to +400° F and 10,000 PSI on liquids from -50° to +500° F ABS, cyclocac, polypropylene, iron, steel or copper.
- Lubricates and seals thread on water, natural gas, steam, air lines, caustics and dilute acids.

48334	1 fl. oz.	Great Blue™ Pipe Joint Compound	038753-483344	12	2
48330	4 fl. oz.	Great Blue™ Pipe Joint Compound	038753-483306	12	7
48331	8 fl. oz.	Great Blue™ Pipe Joint Compound	038753-483313	12	12
48332	16 fl. oz.	Great Blue™ Pipe Joint Compound	038753-483320	24	39
48333	32 fl. oz.	Great Blue™ Pipe Joint Compound	038753-483337	12	40

\*Teflon is a registered trademark of Dupont Fluorocarbon Resins.

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------

**WHITE GENERAL PURPOSE THREAD SEAL TAPE WITH PTFE**

- Provides a clean, positive seal on threaded connections.
- A high density product that resists tearing and stretching for easy, efficient application.
- Available carded or packaged bulk on spools.
- Complies with Military Spec. No. T-27730A & UL31RO.
- 3 mils thick, 0.7 grams/cubic centimeter density.

31199	1/2" x 260"	PTFE tape	038753-311999	144	6
31202	1/2" x 520"	PTFE tape	038753-312026	144	7
31212	3/4" x 260"	PTFE tape	038753-312125	144	6



**YELLOW GAS LINE THREAD SEAL TAPE WITH PTFE**

- Manufactured especially for natural gas, propane, butane, water, oil and chemical lines.
- Heavier than white tape with density of 1.35-1.50 grams/cubic centimeters, 4 mils thick.
- Complies with MIL-T-22230A (ASG), UL 31 RO, AGA 3226 and CAN/ULC-S642.
- Packaged on spools in convenient dispenser box.

31403	1/2" x 260"	Yellow GAS/TFE tape - dispenser pack	038753-314037	100	7
31403D	1/2" x 260"	PTFE Yellow Thread Seal Tape - Display	038753-314037	20	1



**PINK WATER LINE THREAD SEAL TAPE WITH PTFE**

- Provides fast positive seal for water lines, sewage lines and sprinkler systems.
- Effective on metal or plastic threads.
- Complies with MIL-T-27730A.
- Pink tape is 3 mils thick with density of 1.35-1.50 grams/cubic centimeter.
- Packaged on spools in a display carton.

31402D	1/2" x 260"	Pink TFE tape	038753-314020	50	3
--------	-------------	---------------	---------------	----	---



**CLEAR THREAD CUTTING OIL**

- Protection helps make sharp clean threads while extending the life of your dies.
- Formulated for hand thread cutting machines.
- Anti-mist and non-staining formula is not affected by weather.

30200	16 oz.	Clear Cutting Oil (hand threads)	038753-302003	12	13
30201	32 oz.	Clear Cutting Oil (hand threads)	038753-302010	12	26
30202	Gallon	Clear Cutting Oil (hand threads)	038753-302027	6	50



**DARK THREAD CUTTING OIL**

- Formulated for high speed cutting machines.
- A special mixture of sulfonated and chlorinated oils provides high film strength.
- Keeps machines running cooler and extends the life of your dies.
- Anti-mist and non-staining formula is not affected by weather.

30203	16 oz.	Dark Cutting Oil (speed threading)	038753-302034	12	13
30204	32 oz.	Dark Cutting Oil (speed threading)	038753-302041	12	26
30205	Gallon	Dark Cutting Oil (speed threading)	038753-302058	6	50



**ALL PURPOSE LEAK DETECTOR**

- Detects leaks quickly on all types of tubing, valves, cylinders, pressure tanks or other systems under air, gas or oxygen pressure.
- Functions in a -55°F to +160°F temperature range.
- Slow evaporation rate provides longer inspection time.

30209	8 oz.	All Purpose Leak Detector with dauber	038753-302096	24	17
30211	16 oz.	All Purpose Leak Detector with trigger spray	038753-302119	12	17
30212	Gallon	All Purpose Leak Detector	038753-302126	4	39



**PLUMBERS HAND CLEANER**

- Safely removes plastic pipe cements from hands.
- Also removes varnish, enamels, grease and adhesives.
- Use with or without water.
- Freshly scented conditioning formula contains aloe, lanolin, jojoba and vitamin E.

30221	16 oz.	Hand Cleaner - squeeze bottle	038753-302218	12	14
30223	60 oz.	Hand Cleaner - 1/2 gallon w/ dispenser	038753-302232	4	19



Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
-------------	------	-------------	-------------	-----------------	----------



**EPOXY PUTTY**

- Convenient multi-purpose sealing, patching and mending compound.
- Steel filled material, mixes in the hand and hardens in minutes.
- May be drilled, tapped, filed, sanded, sealed and painted when hardened.
- Non-toxic material contains no solvents and will not shrink.

31270	4 oz.	Tubes Epoxy Putty - display	038753-312705	12	4
-------	-------	-----------------------------	---------------	----	---



**TUB-N-TILE CAULK**

- White, flexible, latex sealant.
- Fills and seals cracks and joints.
- For caulking around showers, tubs, lavatories and sinks.
- Cleans up with soap and water.
- Can be used to reset loose tiles.
- Can be painted when dry with either oil base or latex paint.

30240	6 oz.	Tubes - white acrylic latex in bulk pack	038753-302409	24	16
30241	10 oz.	Cartridge - white acrylic latex	038753-302416	24	30



**TUB-N-TILE ULTRA CLEAR SEALANT**

- Applies white and dries clear.
- Flexible butyl acrylate formula adheres to porous surfaces such as wood and masonry.
- Cleans up with soap and water.
- Flexible material won't crack or peel and adheres tightly.
- Paintable with no offensive odors.

30235	6 oz.	Tube - Clear Sealant	038753-302355	12	6
-------	-------	----------------------	---------------	----	---



**SILICONE SEALANT**

- Clear and white sealants for high performance sealing.
- Bonds to porcelain, ceramic marble, fiberglass and most metals.
- Remains permanently elastic.
- When fully cured, recognized by USDA for use in meat and poultry plants.
- Meets Fed. Spec. TT-S-00230C Class A & TT-S-001543A Class A, Mil. Spec. 46106A, ASTM C920, FDA Regulation No. 21 CFR 177.2600.
- Withstands temperature from -60°F to 400°F.

30236	10.3 oz.	Cartridge - Clear Silicone Caulk	038753-302362	12	11
30237	10.3 oz.	Cartridge - White Silicone Caulk	038753-302379	12	11

Product No.	Size	Description	U.P.C. Code	Carton Quantity	Ctn. Wt.
<b>HEAVY DUTY WAX BOWL RING</b>					
		<ul style="list-style-type: none"> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Fits 3" or 4" waste lines and meets Military Spec. TT-P-1536A.</li> </ul>			<ul style="list-style-type: none"> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> </ul>
31190		Heavy Duty wax bowl ring	038753-311906	48	25



<b>HEAVY DUTY WAX BOWL RING W/ SLEEVE</b>					
		<ul style="list-style-type: none"> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Fits 3" or 4" waste lines and meets Military Spec. TT-P-1536A.</li> </ul>			<ul style="list-style-type: none"> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> <li>Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> </ul>
31194		Wax bowl ring with polyethylene sleeve	038753-311944	24	15
31193		Flanged gasket w/brass bolts and nuts	038753-311937	24	17



<b>URETHANE REINFORCED WAX BOWL RING W/ SLEEVE</b>					
		<ul style="list-style-type: none"> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> <li>Fits 3" to 4" waste lines and meets Military Spec. TT-P-1536A.</li> </ul>			<ul style="list-style-type: none"> <li>Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> <li>Urethane sponge provides resiliency. Expands and contracts with the bowl or building to prevent wax from settling.</li> </ul>
31195		Urethane reinforced wax bowl ring with polyethylene sleeve	038753-311951	24	14



<b>MAXWAX® WAX BOWL RING</b>					
		<ul style="list-style-type: none"> <li>40% thicker wax ring with a polyethylene sleeve to assure a tight seal.</li> <li>100% pure petroleum wax gasket for setting any floor type closet bowl.</li> <li>Fits 3" to 4" waste lines and meets Military Spec. TT-P-1536A.</li> </ul>			<ul style="list-style-type: none"> <li>Polyethylene sleeve extends discharge opening for a more positive seal assuring proper bowl alignment.</li> <li>Provides a permanent seal impervious to vermin, odors, gases and acids.</li> </ul>
31188		MaxWax bowl ring with sleeve	038753-311883	12	7



<b>URINAL WAX RING</b>					
		<ul style="list-style-type: none"> <li>Urinal wax ring has a urethane sponge to provide resiliency.</li> </ul>			
31187		Urinal Wax Ring	038753-311876	12	3

