



4700 W. 160th St.  
Cleveland, OH 44135  
PH: 800-321-9532  
FX: 800-321-9535  
www.oatey.com

**TECHNICAL SPECIFICATION**

**DWV J-HOOK®**



**TECHNICAL SPECIFICATION:** Oatey DWV J-Hook® provides fast, easy and economical way to secure drain piping. DWV J-Hooks allow for expansion and contraction of piping systems. DWV J-Hooks can be used on Schedule 30 & 40 piping to support drain, waste and vent piping from joists and rafters. Nail holes on all four sides allow for attachment at various angles for pipe runs.



**LISTINGS AND APPROVAL**



IAPMO Listed

**PHYSICAL/CHEMICAL PROPERTIES**

Material High Impact ABS  
Safe Work Load 50 lbs.  
Temperature Use Rating 240° F

**PRECAUTIONS**

Check with local codes to ensure proper spacing requirements for piping support.

Oatey DWV J-Hooks are for cradle installations only, and are not to be used inverted in any application.

Read cautions and directions on packaging carefully before using this product. KEEP OUT OF REACH OF CHILDREN.

**COMMON APPLICATIONS**

Oatey DWV J-Hook® provides fast, easy and economical way to secure drain piping. DWV J-Hooks allow for expansion and contraction of piping systems. DWV J-Hooks can be used on Schedule 30 & 40 piping to support drain, waste and vent piping from joists and rafters.

PRODUCT NUMBER	DESCRIPTION	PACK	CARTON WEIGHT
33740	1-1/2" x 7" DWV J-Hooks (25 per bag)	300	30 lbs.
33741	2" x 7" DWV J-Hooks (25 per bag)	300	30 lbs.
33742	3" x 7" DWV J-Hooks (25 per bag)	300	31 lbs.
33743	4" x 7" DWV J-Hooks (25 per bag)	300	32 lbs.
33760	1-1/2" x 7" DWV J-Hooks (4 per bag)	6 bags	2 lbs.
33761	2" x 7" DWV J-Hooks (4 per bag)	6 bags	3 lbs.
33762	3" x 7" DWV J-Hooks (4 per bag)	6 bags	3 lbs.
33763	4" x 7" DWV J-Hooks (4 per bag)	6 bags	4 lbs.